

OPERATION & MAINTENANCE

Technocover Security Level 5 Anti-Terrorist Access Doors

Technocover Security Level 5 Anti-Terrorist access doors and frames are manufactured in a minimum 4 mm. steel plate and hot dip galvanised after manufacture to BS EN ISO 1461, a standard which determines that a product has a guaranteed minimum life expectancy. Doors are fitted with a composite material anti attack backing system which may incorporate an integral alarm. ***On no account should any part of the Door or Frame assembly be site drilled, pierced or cut.***

Operation

To open the door...

Unlock and remove the Security padlock and rotate the hinged shroud so that the locking handle is exposed. Turn the locking handle through 90° - the shoot bolts will be released. Pull the door outwards to the fully open position and ensure that the safety stay is properly engaged.

To close the door...

Disengage the safety stay and, with the locking handle in the 'open' position, push the door closed. Turn the locking handle through 90° and ensure that the shoot bolts are properly engaged. Rotate the hinged shroud into position over the staple and re-fit the Security padlock.

Maintenance

The door is totally maintenance free after installation, but extreme substances, such as acids, should not be brought into contact with the door, as they may adversely affect the life expectancy of the galvanising.

Annual inspection is, however, recommended to ensure that the free movement of hinges and effectiveness of safety stays are maintained.

Replacement components may be obtained from Technocover.

For care and maintenance of Padlocks, take manufacturers advice.

(Ref. Document title: DS-AT-5-O&M, Rev: A, Date: May 2015)