

# OPERATION & MAINTENANCE

## Technocover UltraSecure Walk-in Modular Enclosure

Technocover UltraSecure Walk-in Modular Enclosures are manufactured in a minimum 4 mm steel plate and hot dip galvanised after manufacture to BS EN ISO 1461, a standard which determines that a product has a guaranteed minimum life expectancy.

Basic construction of WMC unit: The product consists of multiple wall panels (assembled as a perimeter wall) and include an access door(s) (see below for operation). All wall panels are bolt secured to the inside of the unit. Modular roof panels - spanning across the building - are secured to the underside and include an upturned flange (visible from outside) to enable a waterproof seal to be achieved.

### Operation

If a Padlockable door is fitted...

Please see document "DS-DV-4-O&M"

If a Sentinel door is fitted...

Please see document "DS-SEN-O&M"

### Maintenance

The cabinet is totally maintenance free after installation, but extreme substances, such as acids, should not be brought into contact with the cabinet as they may adversely affect the life expectancy of the galvanising.

Annual inspection is, however, recommended to ensure that the free movement of hinges and effectiveness of safety stays are maintained.

Seals and ventilation mesh (where fitted) should also be checked for damage. Louvres should be kept free of obstruction, such as grass and other vegetation, which may inhibit ventilation.

Replacement components may be obtained from Technocover Ltd.

*(Ref. Document title: WMC-DV-O&M, Rev: A, Date: May 2015)*